



Pro 3

Abrasion

App. 80.000 rubs acc. to the Martindale method,
EN ISO 12947

Pilling

Note 4, EN ISO 12945

Lightfastness

Note 6-7, ISO 105-B02

Flame resistance

AS/NZS 1530.3
BS 5852 part 1
BS 5852 crib 5
DIN 4102 B1
EN 1021-1/2
FAR 25.853
IMO FTP Code 2010:Part 8
NF D 60 013
NF P 92 507 M1
Önorm B1/Q1
SN 198 898 5.2
UNI 9175 1IM
UNI 9177 classe 1
US Cal. Bull. 117-2013

Quality benefits

Very good abrasion
No pilling in use and wash
Very good lightfastness
Can be washed if loose covers
Permanent flame retardant

Environmental benefits

No use of AZO dyes, which may split off carcinogenic acrylamines
No use of dyes containing heavy metals/complies with ETAD norm
No content of formaldehyde
No use of brominated flame retardants
Biodegradable spinning oil
We adhere to the limits set by the the Danish Environmental Protection Agency's "List of undesirable substance
Complies with REACH

Reduced Emissions

Greenguard and Greenguard Gold certified

For further information
kvadrat.dk

Pro 3

Design : Finn Sködt

Composition : 100% Trevira CS

Yarn type : Filament

Binding : Panama

Width : 150 cm

Weight : App. 510 g/lin.m

Repeat : None

Cleaning : Washable at 60°C. Dripdrying.

Shrinkage app. 2%

More info: Maintenance instruction—please see website



10 year
warranty 