



## Twill Weave

### Abrasion

Approximately 60.000 Martindale rubs EN ISO 12947

### Pilling

Note 3-4 EN ISO 12945

### Seam slippage

Warp: 2.5 mm, Weft: 1.7 mm

### Lightfastness

Note 5-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

### Flame resistance

AS/NSZ 1530.3

BS 5852 Crib 5 with treatment

BS 5852 ignition source 3

BS 5852 Part 1

EN 1021-1/2

IMO FTP Code 2010:Part 8

NF D 60 013

SN 198 898 5.3 with treatment

UNI 9175 1IM

US Cal. Bull. 117-2013

### Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### Quality benefits

Very good abrasion

Very good lightfastness

Flame retardant

### Environmental benefits

No use of AZO dyes, which may split off carcinogenic acryl amines

No use of dyes containing heavy metals/ complies with ETAD norm

We adhere to the limits set by the Danish Environmental Protection Agency's 'List of undesirable substances'

Complies with REACH regulation

### Reduced emission

Greenguard and Greenguard Gold certified  
[www.greenguard.org](http://www.greenguard.org)

For further information  
[kvadrat.dk](http://kvadrat.dk)

### Twill Weave

Design: Jonathan Olivares

Type: Upholstery

Composition: 90% new wool, 10% nylon

Yarn type: Worsted

Binding: Twill

Width: 140 cm (app. 55 inches)

Weight: App. 960 g/lin.m

Repeat: None

Cleaning: Vacuuming and dry cleaning

More info: Maintenance instruction—please see website

